



ITALDIBIPACKGROUP

ECOFARD AOL

AUTOMATIC SLEEVE WRAPPING WITH LATERAL FEEDING

Fully automatic sleeve-wrapper with lateral feeding for “multipackage” (several products wrapped up together on several lines) without an operator. Practical high-speed sleeve-wrapping machine able to package a wide range of products (bottles, vases, jars, pots, cans, phials, cases etc) and to shelter boxes integrating and/or replacing the use of carton boxes at end-of-line with great management advantages. The machine is compact and consists in a sealer and a tunnel; it works in a very simple way: a motorized in-feed belt conveyor, situated at 90 ° from the sealing bar, drives the products from the loading area towards the sealing area. Then a transversal sealing-bar (that has a pneumatic movement and temperature is electronically controlled) cuts and seals the film.

SPECIFICATIONS	ECOFARD AOL
Power supply	380 V - 3 Ph + N
Power required	18 KW
Overall machine dimensions L x W x H	4200 x 1500 x 1800 mm
Working plate height	870 mm
Tunnel entrance dimensions	700 x 410 mm
Tunnel length	1400 mm
Machine weight	450 kg
Transverse sealing dimensions	700 mm
Sealing-bar opening	330 mm
Maximum product thickness	400 mm
Maximum roll width	650 mm
Belt conveyor speed	4 m/min
Motorized film-unwinding	Top and bottom roll
Compressed air pressure	6 bar
Output	240 - 480 pcs/h

Note: Technical data subject to variations without prior notice
Output depends on the operator and the type of article to be wrapped.



Arctec (Pty) Ltd.

JHB - 4 Barbeque Terrace, Dytchley Road, Kyalami, Midrand
Tel: +27 11 466 2468 | Fax: +27 11 466 2080
CPT - Unit 25 River Edge Business Park, Winelands Close, Stikland, Bellville
Tel: +27 21 946 4745 | Fax: +27 21 946 2405
www.arctec.co.za | info@arctec.co.za

