

Residential Combustion Analyzer Fyrite® InTech™





Features & Benefits:

- · Easy-to-read, high-contrast LCD display with backlighting
- Low-cost combustion analyzer
- Direct measurement of O₂, CO (0-2,000 ppm), stack and ambient temperature
- Calculated measurement of combustion efficiency CO₂, CO (air-free) and excess air
- Internal data storage of 10 complete records
- Rugged, reliable, long-running performance in a light, handheld unit
- "Plug-n-play" B-Smart® pre-calibrated sensors enable simple in-field replacement, reducing instrument down-time and providing low cost of ownership.



Affordable, Easy-To-Use Combustion Analyzer

Based on the same technology as Bacharach's Fyrite® commercial units, the Fyrite® InTech™ is an advanced, American-made, residential combustion analyzer that delivers guick, accurate measurement of oxygen, carbon monoxide, stack temperature and ambient temperature. It helps to reduce service call times by providing accurate, electronic test results instantly via intuitive, push-button operation and a menu of selectable fuel types. A new, high-contrast LCD graphic display, with backlighting, makes your results easy to see in any environment and can be output via an optional wireless printer and reporting kit.

Designed to calculate the efficiency of residential furnaces and combustion appliances by measuring the stack temperature and the percent oxygen level in the flue-gas stream. The Fyrite® InTech™ also features B-Smart® sensor technology which enables simple, in-the-field pre-calibrated sensor replacement, which minimizes instrument downtime and provides a low cost of ownership.



Quick Payback

The Fyrite® InTech™ reduces service call times by providing accurate, electronic test results instantly

Accurate Operation

Tactile feedback from the instrument's keypad assures that the appropriate key has been pressed

Ergonomically Designed

The instrument is light and fits in the palm of your hand, making it easy to handle.

Long Battery Life

Four alkaline batteries typically offer up to 20 hours of continuous operation with an automatic "power off" feature that saves energy

Featuring B-Smart[®] Sensors

With B-Smart® pre-calibrated CO sensors, contractors can simply replace the instrument's depleted sensor by plugging in a new replacement sensor through an easily accessible port in the back of the unit. The time-saving technology eliminates the need to send in the instrument for calibration or for a new sensor. Your new pre-calibrated sensor will be installed and back on the job in just a few minutes.

Distributed By:

Fyrite® InTech™ Product Specifications

0.1 to a fuel dependent maximum (in %)

Measurement Ranges: 23° F to 113° F (-5° C to 45° C) **Ambient Temperature** -4° F to 1,202° F (-20° C to 650° C) Flue Gas Temperature

0.0% to 20.9% Oxygen (02) 0 - 2,000 ppm Carbon Monoxide (CO)

Calculated Ranges: Combustion Efficiency

Carbon Dioxide (CO2)

Carbon Monoxide (Air Free)

Excess Air

0 to 250% 6 pre-programmed: Natural Gas, Oil #2, Oil #6, Kerosene, B5, **Selectable Fuels:**

0 to 9,999 ppm

0.1 to 100%

and propane/LPG | (10 fuels available with Siegert version)

Up to 10 complete records, internal storage **Data Capability:**

Dimensions: 8.0"h x 3.6"w x 2.3"d (20.3 cm x 9.1 cm x 5.8 cm)

Weight: 16 oz. with batteries (0.45 kg) Power: 4 AA Alkaline batteries (included) Minimum 20 hours, typical battery life **Run Time:** EN 50270, CE mark, EN 50379 (pending) **Approvals:**

Instrument and CO sensor- 2 Years; O₂ Sensor - 1 Year Warranty:

Display Languages Available: English, French, Spanish, Polish, German, Italian, Dutch, Danish

Fyrite® InTech™ Ordering Information

	,
0024-8510 0024-8511	Fyrite [®] InTech [™] (O ₂ Only, includes probe, 4 AA batteries, soft-carry case) Fyrite [®] InTech [™] (CO, O ₂ , includes probe, 4 AA batteries, soft-carry case)
0024-8513	Fyrite [®] InTech™ European Model* (CO, O ₂ , Includes probe, 4 AA batteries, soft-carry case)
0024-8523	Fyrite® InTech™ Kit - without printer (CO, O ₂ , includes rubber boot, probe, 4 AA batteries, hard-carry case)
0024-8512	Fyrite® InTech™ Reporting Kit - (CO, O ₂ , includes printer, rubber boot, probe, 8 AA batteries, hard-carry case, USB cable, Fyrite® User Software, spare filters)
0024-8514	Fyrite [®] InTech [™] Reporting Kit European Model* - (CO, O ₂ , includes printer, rubber boot, probe, 8 AA batteries, hard-carry case, USB cable, Fyrite [®] User Software, spare filters)
	* European based calculations.

Fyrite® InTech™ Replacement Parts & Accessories

0024-1400	IrDA Printer w/ Disposable Batteries
0024-1310	Printer Paper (5 rolls)
0024-1127	Protective Boot with Magnet
0024-0865	Hard Carrying Case
0024-1505	NO _X Filter Kit
0019-3265	Replacement Water Trap/ Filter Assembly (for Probe Assembly)
0007-1644	Replacement Filters for Water Trap (package of 3)





