(b) ITALDIBIPACK

NASTROPACK LINE



NASTROPACK NP 01 LC EV

TAPE-SEALER FOR STANDARD-SIZE CARTON BOXES

A machine for the automatic sealing of standard-size carton boxes (units with f xed height and width). Two simple and fast manual hand- wheel adjustments allow the setting of the machine to the required box size. The bottom and the top f aps are simultaneously sealed (the carton box must be introduced in the machine with the top f aps already closed). Ideal solution for carton boxes with a maximum 50 cm width and height.

SPECIFICATIONS

Side pressure rolls with 3 wheels positioned in multiple places, for a better side pressure of the carton (to keep the upper f aps approach even in the presence of bulging/swollen/f lled cartons)

Millimeter scale f tted as standard on the machine frame, for an easy and quick adjustment of the upper assembly depending on the height of the carton which has to be taped

Device "close three f aps" to facilitate and speed up the inclusion of carton... with a consequent increasing of the productivity

Max width of the cartons: 480 mm

Max height of the cartons: 480 mm

Min width of the cartons: 140 mm

Min height of the cartons: 120 mm

Special solutions available for different sizes

Taping head with a new roll to reduce noise during the detachment of the mother tape, during the conducting of the tape

Blue color (main structure of the machine) and yellow color (moving parts)

NASTROPACK NP 01 TB EV

CASE TAPE MACHINE WITH TOP AND BOTTOM DRIVING SYSTEM

The best solution to close the most unstable carton boxes

SPECIFICATIONS

Appearance: more vivid color, modern, fresh... and still improved machine structure in several small parts

Millimeter scale f tted as standard on the machine frame, for an easy and quick adjustment of the upper assembly depending on the height of the carton which has to be taped

Max width of the cartons: 600 mm

Max height of the cartons: 500 mm

Min width of the cartons: 140 mm

Min height of the cartons: 120 mm

Blue color (main structure of the machine) and yellow (moving parts)

NASTROPACK NP 01 TB EV

E) ITALDIBIPACK



SPECIFICATIONS

Dimensions of the carton boxes:

minimal width 140 mm – maximal width 480 mm minimal height 120 mm - maximal height 500 mm minimal length 150 mm - maximal length without limitation

Simultaneous application of the self-adhesive tape on bottom and on the top side of the carton during its passage through the machine with possibility to adjust the front and the rear leg length

Working tension: single-phase, 220 volts

Compressed air consumption: depending from the specif cations and the dimensions of the carton boxes (indicatively 3,5 - 4 nl/cycle) at a pressure of 6 bar

Side safety panels in transparent execution, protecting the area close to the movement of the upper sealing and driving unit

NASTROPACK NP 03 EV

SEMI AUTOMATIC CARTON SEALING MACHINE

The self-conforming/random-size machines with lateral driving system ideal for every type of carton boxes. The most suitable solution to close automatically different size of carton boxes. Once the carton is f lled and positioned on the machine, after a simple and light pushing the height of the taping unit and the width of the side drive belts automatically adapt to the dimensions of the box itself allowing the carton box to be driven through the machine for the simultaneous application of the self-adhesive tape on the top and on the bottom side. The robust, elegant and "fresh" structure of the machine, together with its characteristics and technical solutions make this machine very appreciated by the wide number of word wide Customers that have selected it for the packing operations.



NASTROPACK NP 03 TB EV

NASTROPACK NP 05 EV

TAPE-SEALER FOR STANDARD-SIZE CARTON BOXES

A machine for the automatic sealing of standard-size carton boxes (units with f xed height and width) with simultaneously sealing of bottom and top f aps of the carton box. An adjustable pneumatic working device assuring the automatic closing of the top f aps gives the possibility to position this machine, not requiring the constant presence of an operator, inside fully automatic packing lines. Two simple and fast manual hand-wheel adjustments allow the setting of the machine to the required box size. The ideal solution for carton boxes with a maximum 50 cm. width and height.

SPECIFICATIONS

Power supply: 230 V - 1 Ph - 50 Hz Power required: 0,6 kW Machine dimensions (LxWxH): 1500x900x1600 mm Machine weight: 280 kg Compressed air consumption: 4 NI / 6 bar Output: up to 20 pz/min



NASTROPACK NP 05 EV



Via Europa, 35 - 20010 Pogliano Milanese - Milano (Italy) tel. +39 02 9396461 - fax: +39 02 93549494

info@italdibipack.com www.italdibipack.com