

ITAG®4

Single Use USB PDF Recording Indicator







ITAG®4 series data loggers are developed to monitor and capture temperature or humidity excursions in pharmaceutical, biological and clinical trial supply chains. With TempSen's advanced measurement technology, user could easily have a reliable monitoring results accurately reflecting the supply chain environmental conditions.

Easy-to-read LCD indication presents key information for immediate decision making, the compact and lightweight design also enables it fits into any limited spaces. Furthermore, automatically generated PDF report allows quick access to shipment data anywhere anytime, and enables efficient supply chain handling, embedded raw could be extracted and studied through TempSen cloud based service.

As a complete software-free cold chain monitoring tool, ITAG4 requires no software for programming, online configuration portal realized the configuration of logger anytime anywhere, higher supply chain disposition efficiency but lower IT investment costs.

It's an ideal electronic recorder that you need to precisely track the environmental conditions that may compromise quality.

Auto PDF Report with Embedded Data

Automatically generated encrypted PDF format report, no software required to access data record, embedded raw data allows further analysis of data via TempCentre and Cold Chain CloudTM.

Software-Free Online Configuration

Allows immediate online configuration, no need to download and install programming software before shipping.

Intuitive LCD Indication


LCD presents all key information regarding recording results, including alarm and running status, monitoring history, alarm violation indication and duration statistics.

FDA 21 CFR 11 Compliance

Designed for FDA 21 CFR part 11 compliance (with TempCentre).

Qualified for Air Transport Monitoring

Complies with RTCA/DO-160G Environmental Conditions and Test Procedures for Airborne Equipment, qualified for air transport in active status.



Туре	Single Use (Pre-programmed/User programmable optional)
Sensor	Internal NTC
Memory Capacity	7200 readings
Measurement Range	-30°C70°C (-22°F158°F)
Accuracy	±0.5°C/0.9°F
Resolution	0.1°C/°F
Start Mode	Manual/Auto
Logging Interval	1 minute2 hours
Alarm Range	High and low alarm
Alarm Type	Single Event/Cumulative Alarm
Battery	3.0V CR2032 lithium battery
Typical Run Time	60 days
Shelf Life	2 years (1 year if activated)
Display	LCD •OK(√), Alarm(x), Running status •Limit violation event indicator •Duration time of each alarm zone •Temperature statistics (max, min, avg)
Connection	USB 2.0 Connector
Automatic Data File	Encrypted PDF report with embedded raw data
Software	TempCentre (21 CFR 11 Compliance)
Calibration	Factory Sampling 6-point Calibration (AQL 0.25)
Certifications	CE, EN12830, RTCA-DO160G, Manufacturer's Validation Certificate
Dimensions	93mm L x 45mm W x 7mm H
Weight	Approx. 25g
Packaging/Material	Case/Polycarbonate
Protection Class	IP65

APPLICATIONS

- Pharmaceuticals / biologicals distribution
- Fruits / Vegetables distribution
- Global wide clinical trail supply chain
- Perishables delivery
- Blood samples delivery



Please learn more about ITAG $^{\scriptsize \scriptsize{0}}$ 4 data logger via www.tempsen.com

TempSen Electronics Company, a leading provider of data loggers & data acquisition systems headquartered in Shanghai, China, is committed to continuously offering a broad range of data monitoring devices and solutions for customers from life science to food industry, helping users employ stringent and effective monitoring measures for temperature sensitive goods in transit and storage. TempSen is an ISO9001:2008 company. TempSen reserves the right to change any specifications and information about products without prior notice. TempSen, ITAG, Tempod are registered trademarks of TempSen Electronics Company. All other trademarks mentioned herein are property of their respective companies.