## **Product Data Sheet**

Published date: 13.06.2013



## 225 Ionising Blower



Product code: 225

The Model 225 Ionising Blower provides a high level of ESD protection with excellent workstation coverage, "quiet" operation and ease of maintenance. The 225 is the top of the range model and is provided with an extensive range of features and options.

## **Benefits Features**

lon balance +/- 5V (+/- 1V when used inconjunction with the remote ioniser controller option)	Provides the highest level of ESD security for sensitive applications.
Dirty pin indicator (LED) and switchable audiblealarm	Detection of a fault triggers a visual and an audible alarm to indicate that maintenance (e.g. emitter pin cleaning) is required.
Separate positive and negative out of balanceindicators with switchable audible alarm	Provides a clear indication of blower status (balance condition).
Auto shutdown	System automatically shuts down when an out of balance or dirty pin condition is encountered to prevent any continuing damage.
Auto tracking alarm	Ensures that alarms are set at the correct levels for the actual operating environment.
Removable titanium emitter pins	Easy maintenance and minimum downtime (unit can be fully maintained without demounting).
Fan speed control (3 speed settings)	Enables optimum set up for operator comfort and ionisation range.
Excellent air flow characteristics	Near laminar flow reduces turbulence and operator discomfort.
RJ11 for remote ion balance control sensor (autoselecting)	Very fine balance in critical applications and nullifies the effects of varying ambient conditions.

## **Technical Characteristics**

Ozone	Less than 0.01ppm
Housing	Powder coated steel
Input connector	IEC socket
Decay time (1,000V to 100V typical)	Less than 4 secs at 457mm at maximum fan speed
Length	600mm or 1200mm as standard

Product shown in this document may be covered by one or more patents, patents applied for and/or registered designs and/or trade marks. For further info please refer to our Head Office or visit www.meech.com.

