ECOFILL HIGH TECH 1



FEATURES

- Table with adjustable tilt.
- Electronic Counter: accuracy + / 0.5%
- Vacuum air and nitrogen injection.
- Touch screen.
- Safety bars and automatic start.
- Equipped with flexible rotor pump.
- SIEMENS PLC.
- Automatic C.I.P. (clean in place).
- CE Homologation.

Single head filler, automatic and equipped with an electronic counter.

ECOFILL HT1 is a latest generation filler, fast, accurate and very easy to use uncap, air vacuum, filling, nitrogen purge, recap and automatic ejection.

The operator will feed de machine with a bag and the machine will then automatically start, uncapping the bag, following with the air vacuum, filling, nitrogen purge, and ejection at the end of the process.

Meanwhile the operator has time enough to close the box or palletize the Bag in Box packages.

Stainless steel structure, equipped with the last generation electronic and pneumatic components provide maximum reliability and performance.

Touch screen, safety bars, automatic start and flexible rotor centrifugal pump.

Ecofill HT1 can be connected to our **ECOPACK MASTERFORM** carton erector machine, our **ECOPACK HOTMELT** case closer machine and to our **SPEED BOX** palletizer machine.

ACCESSOIRES

- Cabin of positive laminar air flow.
- E.S.L. (extended shelf live) with peroxide injection.
- Mass or electromagnetic counter.
- Intermediate tank with simple level control or pressurized.
- Wheels for easy transport.
 - Dimensions: 800 x 900 x 2.000 mm
 - Weight: 150 Kg

SUPPLIES

- Power: 220V <6AMP</p>
- Air supply: 6 bars minimum
- PRODUCTION
- 3L 7/8 units/minute
- 5L 7 units/minute
- 10L 5 units/minute
- 20L 3/4 units/minute

CARTOBOL reserve his right to change any data or specification described without prior notice.

